

**DIMENSIONS:**

Width: max. 2.00 m, Length: custom, recommended minimum width for wheelchair users: > 1.30 m, various shapes possible

ANCHORING:

Ground anchoring using chain segments flexible positioning possible

MAT COLORS:

Neon green, dark green, blue, yellow, red, pink, beige, black

SUITABLE SURFACES:

Grass, sand, gravel, suitable for all impact protection surfaces

SCOPE OF DELIVERY:

1x Inclusion Mat
max. width: 2.00 m, custom length, various shapes available

chain around the perimeter at 60 cm intervals for ground anchoring

EASY INSTALLATION:

Solution for transitions through optional integration of a flat rubber element.

ADVANTAGES:

- + easy to install
- + simple cleaning
- + robust and stable
- + low maintenance


Quick. Safe. Accessible.

EASY INSTALLATION – STEP BY STEP




1. PREPARE

Level the ground,
remove obstacles



2. LAY OUT

Position and align the mat



3. FIX

Anchor to the ground
using chains (length 60 cm)



4. TRANSITION ELEMENT

Optional Rubber strip
for smooth transitions

Installation instructions
available upon request:
seiltechnik@huck.net

Impact protection
requirements are not
negatively affected by
placing the Inclusion
Mat on top. HIC values
available upon request.



INSTALLATION TIME:

a few minutes

MATERIAL RECOMMENDATION:

Sand 0.2 – 2 mm / Gravel 2 – 8 mm

ADAPTABLE:

conforms to uneven surfaces

BARRIER-FREE:

optional transition element available

Our Inclusion Mat can be permanently and securely installed – either directly on the ground or with an additional transition element for a particularly comfortable, barrier-free access.

